

NCS Model Current Transducer for Industry

Technical Parameter			额定电流	最大输入电流	输出电流	输出电流	输出电流	输出电流	供电电压	精度	绝缘强度		
		REF	I_{PN}	I_{PMAX}	I_{S1}	I_{S2}	V_{S1}	V_{S2}		at I_{PN} (@+/-25° C)	(50 HZ 1min)		
			KA dc	KA dc	mA	mA	V	V	Vdc	%	KV		
Industry	NCS125	连接器	NCS125-2	2	10	+/-20	+/-20	+/-10	+/-10	+/-15 to +/-24 (2%)	<= (+/-) 1	5	
			NCS125-4	4	20	+/-20	+/-20	+/-10	+/-10		<= (+/-) 1	5	
			NCS125-6	6	10	+/-20	+/-20	+/-10	+/-10		<= (+/-) 1	5	
			NCS125-10	10	30	+/-20	+/-20	+/-10	+/-10		<= (+/-) 1	5	
		电缆电流输出	NCS125-2AF	2	10	+/-20	+/-20	-	-		<= (+/-) 1	5	
			NCS125-4AF	4	20	+/-20	+/-20	-	-		<= (+/-) 1	5	
			NCS125-6AF	6	10	+/-20	+/-20	-	-		<= (+/-) 1	5	
			NCS125-10AF	10	30	+/-20	+/-20	-	-		<= (+/-) 1	5	
		电压电流输出	NCS125-2VF	2	10	-	-	+/-10	+/-10		<= (+/-) 1	5	
			NCS125-4VF	4	20	-	-	+/-10	+/-10		<= (+/-) 1	5	
	NCS125-6VF		6	10	-	-	+/-10	+/-10	<= (+/-) 1		5		
	NCS125-10VF		10	30	-	-	+/-10	+/-10	<= (+/-) 1		5		
	NCS165		连接器	NCS165-4	2	20	+/-20	+/-20	+/-10		+/-10	<= (+/-) 1	5
				NCS165-6	4	30	+/-20	+/-20	+/-10		+/-10	<= (+/-) 1	5
		NCS165-10		6	30	+/-20	+/-20	+/-10	+/-10		<= (+/-) 1	5	
		NCS165-20		10	40	+/-20	+/-20	+/-10	+/-10		<= (+/-) 1	5	
		电缆电流输出	NCS165-4AF	2	20	+/-20	+/-20	-	-		<= (+/-) 1	5	
			NCS165-6AF	4	30	+/-20	+/-20	-	-		<= (+/-) 1	5	
			NCS165-10AF	6	30	+/-20	+/-20	-	-		<= (+/-) 1	5	
			NCS165-20AF	10	40	+/-20	+/-20	-	-		<= (+/-) 1	5	
电压电流输出		NCS165-4VF	2	20	-	-	+/-10	+/-10	<= (+/-) 1	5			
		NCS165-6VF	4	30	-	-	+/-10	+/-10	<= (+/-) 1	5			
	NCS165-10VF	6	30	-	-	+/-10	+/-10	<= (+/-) 1	5				
	NCS165-20VF	10	40	-	-	+/-10	+/-10	<= (+/-) 1	5				
	Tracton	NCS125	电缆电流输出	NCS125T-2AF	2	10	+/-20	+/-20	-	-	<= (+/-) 1	20	
				NCS125T-6AF	4	20	+/-20	+/-20	-	-	<= (+/-) 1	20	
NCS125T-10AF				6	30	+/-20	+/-20	-	-	<= (+/-) 1	20		
NCS125T-20AF				10	30	+/-20	+/-20	-	-	<= (+/-) 1	20		
电压电流输出			NCS125T-2VF	2	20	-	-	+/-10	+/-10	<= (+/-) 1	20		
			NCS125T-6VF	4	30	-	-	+/-10	+/-10	<= (+/-) 1	20		
NCS165		电缆电流输出	NCS125T-2AF	4	20	+/-20	+/-20	-	-	<= (+/-) 1	20		
			NCS125T-6AF	6	30	+/-20	+/-20	-	-	<= (+/-) 1	20		
			NCS125T-10AF	10	40	+/-20	+/-20	-	-	<= (+/-) 1	20		
			NCS125T-20AF	20	40	+/-20	+/-20	-	-	<= (+/-) 1	20		
电压电流输出	NCS125T-2VF	2	20	-	-	+/-10	+/-10	<= (+/-) 1	20				
	NCS125T-6VF	4	30	-	-	+/-10	+/-10	<= (+/-) 1	20				
	NCS125T-10VF	6	40	-	-	+/-10	+/-10	<= (+/-) 1	20				
	NCS125T-20VF	10	40	-	-	+/-10	+/-10	<= (+/-) 1	20				